



75740101



**IP20**



### KNX Touch Control TFT display, intg bus coupling unit, KNX, black glossy

#### Technical Features

#### Installation, mounting

|             |                |
|-------------|----------------|
| Mounting on | Flush mounting |
|-------------|----------------|

#### Use conditions

|                       |           |
|-----------------------|-----------|
| Operating temperature | 0 - 50 °C |
|-----------------------|-----------|

#### Electric current

|                                       |       |
|---------------------------------------|-------|
| Bus current consumption data transfer | 10 mA |
|---------------------------------------|-------|

#### Dimensions

|                                    |          |
|------------------------------------|----------|
| Built-in depth                     | 25.50 mm |
| Built-in depth flush-mounted boxes | 29 mm    |
| Height                             | 75 mm    |
| Width                              | 95 mm    |
| Depth                              | 44 mm    |

#### Equipment

|                            |   |
|----------------------------|---|
| Number of actuation points | 6 |
|----------------------------|---|

#### Materials

|                |                  |
|----------------|------------------|
| Colour         | Black            |
| RAL code       | 9005             |
| Material       | Metal<br>Plastic |
| Surface finish | Glossy           |

#### Screen

|              |     |
|--------------|-----|
| With display | Yes |
|--------------|-----|

#### Texts

|          |                                                                                                                                                                                                                                                                                                                                                                                                                   |
|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Function | 16 time switching functions and alarm clock<br>Logic modules: 4x AND, 4x OR with 4 inputs each<br>Functions such as switching, dimming, blind control, up to 16 scenes, climate control, activation of alarm systems, date, time of day<br>Automatic function for control of lighting, blinds and roller shutters, air conditioning and ventilation systems<br>Disabling function for cleaning the user interface |
|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

#### Scope of delivery

|                         |     |
|-------------------------|-----|
| Bus connection included | Yes |
|-------------------------|-----|

#### Sustainability

|                 |     |
|-----------------|-----|
| Halogen free    | Yes |
| REACH-SVHC free | Yes |
| RoHS conform    | Yes |